

The Problems with indexed_search and how to fix 'em

Jochen Weiland
TYPO3 Conference Dallas, 2010

jweiland.net

3 Search Functions

- Standard Search
- solr
- indexed_search

Standard Search

Suchergebnis: 1-1 von 1

Home

Bei der Entwicklung wurde darauf Wert gelegt, nicht nur irgendeine Beispieleseite zu entwickeln, sondern eine modernes Template, das dem aktuellen Stand der Technik entspricht und praxistauglich ist. ...

Suchwort:

Suchen in:

Suchen!

- Slow
- Headlines and text from tt_content
- No advanced search
- No external documents

TYPO3 solr

- "Google for TYPO3"
- Fast, powerful
- Requires separate Index-Server (Apache Tomcat)

indexed_search

- Fast (if configured right)
- external Files (pdf, doc, xls, txt, ...)
- Problems with re-indexing

Delete Search Index

- TRUNCATE `index_fulltext`;
- TRUNCATE `index_grlist`;
- TRUNCATE `index_phash`;
- TRUNCATE `index_rel`;
- TRUNCATE `index_section`;
- TRUNCATE `index_words`;

```
<body>
  <div id="fullheightcontainer">
    <div id="content">
      <div id="contentWrap"> </div>
      <div id="leftmenu"> </div>
    </div>
    <div id="header"> </div>
    <div id="logo"> </div>
    <div id="rootline"> </div>
    <div id="search"> </div>
    <div id="printlink"> </div>
    <div id="servicemenu"> </div>
    <div id="language"> </div>
  </div>
  <div id="footer"> </div>
</body>
```

```
<body>
  <div id="fullheightcontainer">
    <div id="content">
      <div id="contentWrap"> </div>
      <div id="leftmenu"> </div>
    </div>
    <div id="header"> </div>
    <div id="logo"> </div>
    <div id="rootline"> </div>
    <div id="search"> </div>
    <div id="printlink"> </div>
    <div id="servicemenu"> </div>
    <div id="language"> </div>
  </div>
  <div id="footer"> </div>
</body>
```

```
<body>
  <div id="fullheightcontainer">
    <div id="content">
      <!--TYPO3SEARCH_begin-->
        <div id="contentWrap"> </div>
      <!--TYPO3SEARCH_end-->
        <div id="leftmenu"> </div>
    </div>
    <div id="header"> </div>
    <div id="logo"> </div>
    <div id="rootline"> </div>
    <div id="search"> </div>
    <div id="printlink"> </div>
    <div id="servicemenu"> </div>
    <div id="language"> </div>
  </div>
  <div id="footer"> </div>
</body>
```

```
<body>
  <div id="fullheightcontainer">
    <div id="content">
      <!--TYPO3SEARCH_begin-->
        <div id="contentWrap"> </div>
        <div id="leftmenu"> </div>
      </div>
      <div id="header"> </div>
      <div id="logo"> </div>
      <div id="rootline"> </div>
      <div id="search"> </div>
      <div id="printlink"> </div>
      <div id="servicemenu"> </div>
      <div id="language"> </div>
    </div>
    <div id="footer"> </div>
  </body>
```

```
<body>
  <div id="fullheightcontainer">
    <div id="content">
      <div id="contentWrap"> </div>
      <div id="leftmenu"> </div>
    </div>
    <div id="header"> </div>
    <div id="logo"> </div>
    <div id="rootline"> </div>
    <!--TYPO3SEARCH_end-->
    <div id="search"> </div>
    <div id="printlink"> </div>
    <div id="servicemenu"> </div>
    <div id="language"> </div>
  </div>
  <div id="footer"> </div>
</body>
```

```
<body>
  <div id="fullheightcontainer">
    <div id="content">
      <!--TYPO3SEARCH_begin-->
        <div id="contentWrap"> </div>
      <!--TYPO3SEARCH_end-->
        <div id="leftmenu"> </div>
    </div>
    <div id="header"> </div>
    <div id="logo"> </div>
    <div id="rootline"> </div>
    <!--TYPO3SEARCH_begin-->
      <div id="search"> </div>
      <div id="printlink"> </div>
    <!--TYPO3SEARCH_end-->
      <div id="servicemenu"> </div>
      <div id="language"> </div>
    </div>
    <div id="footer"> </div>
  </body>
```

Speed

```
plugin.tx_indexedsearch._DEFAULT_PI_VARS.type = 0
```

Page Browser not working?

- In Template replace

```
<form action="###ACTION_URL###"  
method="post" id="tx_indexedsearch">
```

with

```
<form action="###ACTION_URL###"  
method="post" name="tx_indexedsearch">
```

Crawler Re-Index

- tx_crawler.crawler{fg.paramSets.index = &contentId=[_TABLE:tt_content]}
tx_crawler.crawler{fg.paramSets.index {
 procInstrFilter = tx_indexedsearch_reindex
 baseUrl = http://user60.t3sem.de/
}}

Crawler Re-Index

- tx_crawler.crawlerCfg.paramSets.index-news =
&tx_ttnews[backPid]=14&tx_ttnews[pointer]=1
&tx_ttnews[pointer]=1
&tx_ttnews[tt_news]=[_TABLE:tt_news;_PID:11]
PID 11 is "news storage folder"

```
tx_crawler.crawlerCfg.paramSets.index-news {  
    procInstrFilter = tx_indexedsearch_reindex  
    cHash = 1  
    pidsOnly = 12 # PID 12 is "news single view"  
    baseUrl = http://user60.t3sem.de/  
}
```

Invoke Crawler

- `typo3/cli_dispatch.phpsh crawler_im 1 -d=10 -conf index -n 10000 -o queue`

`cli_dispatch.phpsh crawler_im 1 -d=10 -conf index-news -n 10000 -o queue`

`/typo3/cli_dispatch.phpsh crawler`

- Download Presentation:

<http://jweiland.net/t3con10>

- Vote and comment:

<http://joind.in/talk/view/1678>

Questions?

jweiland.net